

REVLANE REGULATEUR

ACRYLIC SUBSTRATE PREPARATION



DESCRIPTION

Clear or coloured, ready-to-use liquid designed to adjust the base absorption to render backings, prior to the application of acrylic (Revlane range) coatings.

SUBSTRATES

SUITABLE FOR

- In situ and pre-formed concrete.
- Base coats in accordance with BS 5262.
- PAREXLANKO grey one-coat renders e.g. Parmurex/ Parex waterproofing undercoat systems.
- PAREXLANKO PARISO range of External Thermal Insulation Systems.
- Internal walls, plaster (gypsum) substrates.

TECHNICAL CHARACTERISTICS

COMPOSITION

Apparent density: 1.4 kg/dm³.

EQUIPMENT REQUIRED

- Woollen roller, brush.

Clean all tools with water after the application.

PRODUCT PREPARATION

- Thoroughly mix the product in the bucket until it is of an even consistency.

PAREX

The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not covered by this document are used, customers must request specific additional information and/or carry out a representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.

APPLICATION

- Apply REVLANE REGULTEUR using a woollen roller or brush.
- Allow to dry for 2 to 12 hours according to the temperature and the substrate, before applying the thick plastic coating.

CONSUMPTION

- 150 to 250 g/m² per layer.

PRECAUTIONS

- For professional use only.
- Do not apply to a frozen substrate, where there is a risk of frost, on wet substrates, in rain or foggy weather or if there is a strong, hot and dry wind.
- Temperature range: +5°C to + 30°C.
- On powdery or pulverised substrates (except external thermal insulation systems from the PARISO range), apply REVLANE FIXATEUR before using REVLANE REGULTEUR.



PACKAGING

20 kg bucket.
5 kg bucket.

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions. Store away from high temperatures and sources of heat.

PRECAUTIONS

Read and follow the guidelines in the Health and Safety datasheet for this product.

TECHNICAL ASSISTANCE

ParexLanko will, on request, provide information and assistance to companies in relation to the use of a specific product.

Such assistance shall not be associated with structural and design conception, nor assume or accept liability for compliance of substrates, nor compliance to instructions provided.

Technical Information

0845 603 5530

LOCAL RATE CALL

Download the technical datasheet and consult the health and safety document on our new site: www.parex.co.uk