

TEXTURED FINISHES

PARISO THIN COAT ACRYLIC SYSTEM

DESCRIPTION

- 100 percent acrylic-based textured finish.
- DPR (Dirt Pick-up Resistance): The surface of the finish hardens and does not soften again under heat. The non-tacky surface provides high resistance to accumulation of dirt, mould, and pollutants.
- Integrally coloured with high quality pigments.

USES:

Exterior or interior finish coat over:

- Parex Exterior Insulation and Finishing Systems.
- Properly prepared external masonry, render, concrete surfaces and render receiver boards.
- Interior applications over drywall, plaster, or properly prepared masonry, render, concrete surfaces and render receiver boards.

COMPOSITION:

- Binder base: 100 percent acrylic polymer with surface-hardening properties.
- Aggregate: Pure crushed marble, rust free.
- Water-based.
- Pigment Base: Titanium dioxide.
- Colour: Parex standard colours or tinted to desired custom colours.

NOTE:

"The Plus" Advantage can be added to any Parex finish or coating. "The Plus" provides additional protection against mildew and algae growth.

Finishes can be silicone enhanced to improve the product performance against dirt pick-up and pollution.



Sand stone



Sand fine



Sand coarse



Swirl fine



Swirl coarse



Multi Texture

APPLICATION

- Always maintain a wet edge and work to corners or joints. For best colour consistency, use finish with the same batch number within a wall section. Keep container closed when not in use.
- Application: use a clean stainless steel trowel and apply a uniform coat the thickness of the largest aggregate size of the finish. For Parex **Multi-Texture** finishes, apply a coat slightly thicker than the largest aggregate size.
- Texturing the **Multi-Texture** finish: Follow the first application with a second application of **Multi-Texture** finish, using tools and techniques necessary to obtain the desired texture. The maximum thickness within the applied texture must not exceed 5 mm with average thickness of 3 mm.
- **Swirl** and **Sand** Finishes: Use a clean plastic float or stainless steel trowel. A plastic float will roll the large aggregates more than a stainless steel trowel. Continuously dry clean the plastic float or steel trowel while texturing. Use consistent pressure and motion to achieve the desired texture. See Parex application guides.
- Texturing **Sprayed Smooth** finish: To achieve a consistent texture, **Sprayed Smooth** finish should be sprayed. Trowelling, following the **Sprayed Smooth** application, is not recommended as a uniform smoothness will not be achieved.

LIMITATIONS:

- Ambient and surface temperature must be 4°C or above during application and drying time. Supplemental heat and protection from rainfall must be provided as required.
- Use only on surfaces that are sound, clean, dry, unpainted, and free from any residue which may affect the ability of the finish to bond to the surface.
- Avoid application in direct sunlight in hot weather.

PAREX

The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not covered by this document are used, customers must request specific additional information and/or carry out a representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.